



DOSATRON®

WATER POWERED DOSING TECHNOLOGY

20 GPM: D45RE3000

Product Specifications

Call 800-523-8499 to order the Dosatron for your specific application

| | |
|-------------------------------------|--|
| Dilution Range: | 1:3000 to 1:1000 (.03% to .1%) |
| Water Flow Range: | .4 to 20 GPM |
| Operating Pressure Range: | 7 to 70 PSI |
| Available Housing Materials: | Polyacetal (Standard Blue) |
| Dimensions: | 24" x 7 1/2" |
| Weight: | 8 lbs |
| Connection Size: | 1" NPT |
| Maximum Temperature: | 104° F |
| Included Accessories: | 6 ft clear suction tube, strainer, weight, mounting bracket and operating manual |
| Recommended Accessories: | 200 mesh filter, check valve, pressure regulator, flow restrictor. |



Recommended Installation

IPK100 - 20 GPM Industrial Plumbing Kit



- 1" polypropylene Banjo single union ball valve
- 1/2" stainless steel ball valve
- 1" poly 200 mesh tee filter
- 1" brass pressure regulator w/gauge
- 1" 20 GPM flow restrictor
- 1" polypropylene check valve
- 1" unions PVC schedule 80
- 1" x 2" Banjo polypropylene fittings
- 1/2" x 2" Banjo polypropylene fittings
- 1/2" x 1/2" Banjo barb fitting
- 1" to 3/4" Banjo reducer bushing
- 3/4" male to 1/2" female Banjo reducer bushing
- 1" Banjo T
- 1" Banjo street elbows
- Roll of teflon tape
- Instruction card
- Zip tie



Dosatron International
2090 Sunnydale Blvd. • Clearwater, FL, USA
800-523-8499 • www.dosatronusa.com

Dosatron International, Inc. is an industry leader in water-powered, proportional chemical injectors. Dosatron products are manufactured according to ISO 9001:2000 and ISO 14001:2004 standards.