

# 3 GPM: D07RE125

#### PRODUCT DESCRIPTION

The water-powered Dosatron **D07RE125-3 GPM** injector is easy to install with an Industrial Plumbing Kit (IPK34-3GPM) and has a flow of 0.02 to 3 GPM with a ratio range of 1:667 to 1:80.



Dilution Range:	1:667 to 1:80 (0.15% to 1.25%)
Water Flow Range:	0.02 to 3 GPM
<b>Operating Pressure Range:</b>	4.3 to 85 PSI
Available Housing Materials:	<ul><li>Polypropylene (Standard Blue)</li><li>PVDF (White)</li></ul>
Dimensions:	10" x 4 1/2"
Weight:	2 lbs
Connection Size:	3/4" NPT
Maximum Temperature:	104 <sup>o</sup> F
Included Accessories:	6' clear suction tube, strainer, weight, mounting bracket and operating manual
Recommended Accessories:	200 mesh filter, check valve, pressure regulator, flow restrictor



### **MAINTENANCE KITS**

Injection Seal Kit (PART # PJDI106 - For serial # over 05370953) - For yearly maintenance

Call 800-523-8499 to order the Dosatron for your specific application



# 3 GPM: D07RE125

### **Recommended Installation for Industrial Applications**

#### IPK34 - 3 GPM Industrial Plumbing Kit



3/4" polypropylene single union ball valve

1/2" stainless steel ball valve

3/4" polypropylene 200 mesh tee filter

3/4" brass pressure regulator w/gauge

3/4" 3 GPM flow restrictor

3/4" polypropylene check valve

3/4" union schedule 80 PVC

3/4" x 2" polypropylene fittings

1/2" x 2" polypropylene fittings

1/2" x 1/2" barb fitting

3/4" male to 1/2" female reducer bushing

3/4" Tee

3/4" street elbows

Roll of Teflon tape

Instruction card

Zip tie

Dosatron International 2090 Sunnydale Blvd. • Clearwater, FL, USA 800-523-8499 • www.dosatronusa.com