



Customer Service - Service Clientèle (North & Central America)
 2090 SUNNYDALE BLVD. CLEARWATER - FL 33765 - USA
 Tel. 1-727-443-5404 / 1-800-523-8499 - Fax 1-727-447-0591
 Site web: www.dosatronusa.com

Customer Service - Service Clientèle (Worldwide - Europe)
 Rue Pascal - B.P. 6 - 33370 TRESSES (BORDEAUX) - FRANCE
 Tel. 33 (0)5 57 97 11 11
 Fax: 33 (0)5 57 97 11 29 / 33 (0)5 57 97 10 85
 info@dosatron.com - www.dosatron.com

DOSATRON INTERNATIONAL S.A.S.
 Certified EHSS System
 Manufactured by - Fabriqué par :

This document does not form a contractual engagement on the part of Dosatron International and is for information only. Dosatron International reserves the right to alter product specification or appearance without prior notice.
 © DOSATRON INTERNATIONAL S.A.S 2019

RECOMMENDATIONS

DO NOT USE THIS UNIT WITHOUT A 60 MICRON [300 MESH] WATER FILTER* OR YOUR WARRANTY WILL BE VOID.

*The 60 micron [300 mesh] water filter (sold separately) protects your unit from debris in the water that causes scoring to the piston and housing.

KNOW YOUR WATER FLOW! GRADUALLY TURN ON THE WATER.

COUNT THE NUMBER OF CLICKS IN 15 SECONDS. DO NOT EXCEED 45* CLICKS.

CLICK CHART

Clicks/15 sec	l/h	gpm
2	1250	5,5
4	2500	11
8	5000	22
16	10000	44
30	20000	88
45	30000	132

⚠️ MAXIMUM PRESSURE 8 bar [116 psi]

ET394/QSU/D30-FR-EN/06/19

NEED HELP ?
 Contact your DOSATRON distributor for service or parts

App Store **Google play**

For complete information on the features and operations, refer to your Manual on www.dosatron.com or download our DOSATRON app

IMPORTANT NOTES

Congratulations on your new Dosatron.
 Please read the following important information.

QUICK START UP
D30
30 m³/h - 132 US gpm

⚠️ CAUTION

- When connecting a DOSATRON either to the public water supply or to its own water source, you must respect the regulations in force concerning protection of the source i.e. backflow prevention, etc.
- Contact local authorities for requirements of backflow prevention.
- When installing, operating, and maintaining the DOSATRON water powered metering pump, keep safety considerations foremost. Use proper tools, protective clothings, and eye protection when working on the equipment and install the equipment with a view toward ensuring safe operation.
- Follow the instructions in the manual and take additional safety measures appropriate to the liquid being pumped and the temperature of the water that powers the DOSATRON. Be extremely careful in the presence of hazardous substances (e.g. corrosives, toxins, solvents, acids, caustic, flammables, etc.).
- Before applying any aggressive chemicals, please consult your distributor to confirm compatibility with the dosing pump.

⚠️ Hand tighten. No tools needed.

<p>1</p>	<p>2a</p>	<p>2b</p>
<p>3</p>	<p>4</p>	<p>5</p>

<p>1</p>	<p>2a</p>	<p>2b</p>
<p>3</p>	<p>4</p>	<p>5</p>

Maximum: 45 clicks/15 sec.

6 PRINCIPE D'INSTALLATION / INSTALLATION HINTS

Si le sens de l'eau du Dosatron est identique à votre installation :
Le montage peut s'opérer

The direction of the water flow in the Dosatron unit is identical to that of your water supply system:
The unit can be directly installed

Le contenant produit ne doit pas être positionné au dessus de la pompe doseuse

Chemical tank must not be above Dosing pump level

Si possible, ne pas placer le contenant « produit » directement sous le Dosatron

When possible, DO NOT PLACE the container directly under the DOSATRON

A

Si le sens de l'eau est inversé :
Ouvrir le coffret

The water flows in the opposite direction:
Open the casing

Dévisser le Doseur (1)
Dévisser le régulateur Dosatron (2)
Unscrew the Dosatron unit (1)
Unscrew the Dosatron regulator (2)

B

Revisser l'ensemble sur l'autre partie du coffret (3)
Rescrew it at the other end of the casing (3)

C

Le montage peut s'opérer
The unit can be directly installed