



DOSATRON®

WATER POWERED DOSING TECHNOLOGY

8.8 GPM: D25RE10

PRODUCT DESCRIPTION

The water-powered Dosatron **D25RE10 - 8.8 GPM** injector is easy to install with an Industrial Plumbing Kit (IPK34-7GPM). The water flow range is 0.05 to 8.8 GPM and a dilution range of 1:33 to 1:10.

PRODUCT SPECIFICATIONS

Dilution Range:	1:33 to 1:10 (3% to 10%)
Water Flow Range:	0.05 to 8.8 GPM
Operating Pressure Range:	4.3 to 58 PSI
Available Housing Materials:	Polyacetal (Standard Blue)
Other Options:	Side-inject
Dimensions:	14" x 6 1/4"
Weight:	4 lbs
Connection Size:	3/4" NPT
Maximum Temperature:	104° F
Included Accessories:	4' clear suction tube, strainer, weight, mounting bracket and quick start guide
Recommended Accessories:	200 mesh filter, check valve, pressure regulator, flow restrictor



MAINTENANCE KITS

Injection Seal Kit (Part #: PJ120) - For yearly maintenance

Call 800-523-8499 to order the Dosatron for your specific application



DOSATRON®

WATER POWERED DOSING TECHNOLOGY

8.8 GPM: D25RE10

Recommended Installation

IPK34 - 7 GPM Industrial Plumbing Kit



- 3/4" polypropylene single union ball valve
- 1/2" stainless steel ball valve
- 3/4" poly 200 mesh tee filter
- 3/4" brass pressure regulator w/gauge
- 3/4" 7 GPM flow restrictor
- 3/4" polypropylene check valve
- 3/4" union schedule 80 PVC
- 3/4" x 2" polypropylene fittings
- 1/2" x 2" polypropylene fittings
- 1/2" x 1/2" barb fitting
- 3/4" male to 1/2" female reducer bushing
- 3/4" Tee
- 3/4" street elbows
- Roll of Teflon tape
- Instruction card
- Zip tie

Dosatron International
2090 Sunnysdale Blvd. • Clearwater, FL, USA
800-523-8499 • www.dosatronusa.com