



# DOSATRON®

WATER POWERED DOSING TECHNOLOGY

## 3 GPM: D07RE5

### PRODUCT DESCRIPTION

The water-powered Dosatron D07RE5-3 GPM injector is easy to install with an Industrial Plumbing Kit (IPK34-3GPM) and has a flow of 0.02 to 3 GPM with a ratio range of 1:128 to 1:18.

### PRODUCT SPECIFICATIONS

Dilution Range:	1:128 to 1:18 (0.8% to 5.5%)
Water Flow Range:	0.02 to 3 GPM
Operating Pressure Range:	4.3 to 85 PSI
Available Housing Materials:	<ul style="list-style-type: none"><li>• Polypropylene (Standard Blue)</li><li>• PVDF (White)</li></ul>
Dimensions:	10" x 4 1/2"
Weight:	2 lbs
Connection Size:	3/4" NPT
Maximum Temperature:	104° F
Included Accessories:	6' clear suction tube, strainer, weight, mounting bracket and operating manual
Recommended Accessories:	200 mesh filter, check valve, pressure regulator, flow restrictor



### MAINTENANCE KITS

Injection Seal Kit (Part #: PJDI095) - For yearly maintenance

**Call 800-523-8499 to order the Dosatron for your specific application**



**DOSATRON®**

*WATER POWERED DOSING TECHNOLOGY*

## 3 GPM: D07RE5

### Recommended Installation for Industrial Applications

#### IPK34 - 3 GPM Industrial Plumbing Kit



- 3/4" polypropylene single union ball valve
- 1/2" stainless steel ball valve
- 3/4" polypropylene 200 mesh tee filter
- 3/4" brass pressure regulator w/gauge
- 3/4" 3 GPM flow restrictor
- 3/4" polypropylene check valve
- 3/4" union schedule 80 PVC
- 3/4" x 2" polypropylene fittings
- 1/2" x 2" polypropylene fittings
- 1/2" x 1/2" barb fitting
- 3/4" male to 1/2" female reducer bushing
- 3/4" Tee
- 3/4" street elbows
- Roll of Teflon tape
- Instruction card
- Zip tie

Dosatron International  
2090 Sunnydale Blvd. • Clearwater, FL, USA  
800-523-8499 • [www.dosatronusa.com](http://www.dosatronusa.com)